

nanou

19" LCD CCTV MONITOR

(VGA, BNC, S-VHS)

Model: NO1901



19" LCD Monitor for CCTV industry

- **Inputs : BNC in/out, Audio in/out, S-VHS, VGA**
 - **Resolution : 1280 x 1024**
 - **Built-in 12V DC Power**
- **110V/240V, 50Hz/60Hz Adapter Available**
 - **NTSC/PAL**
- **Brightness : 400cd/m², Contrast : 600:1**
 - **Viewing angle : 140/140**
 - **Wall Mount : VESA 100mm**
- **Option: LCD Wall Mount, Ceiling Mount**



www.nanovdisplay.com

SPECIFICATION

Model: NO1901

19" CCTV LCD Monitor

1. Feature

- High Resolution : 1280x1024@75Hz
- Viewing Angle : 140°(H) x 140°(V)
- Brightness: 400cd/m²
- Contrast ratio: 600:1
- Inputs: Composite Video(BNC), S-Video, PC(VGA), Audio Inputs
- Speakers: 2Wx2W
- VESA Wall-Mountable
- Anti-glare and Hard Coating screen

2. Specifications

LCD Panel	Display Area	376.32mm(H) x 301.05mm(V)
	Type	Active Matrix Super TFT LCD
	View Angel	Left/Right/Up/Down 70/70/75/65
	Screen Coating	Anti Glare and Hard Coating
	Luminance	400cd/?
	Contrast Ratio	600:1
	Pixel Pitch	0.294mmx0.294mm
	Color Combinations	16.7 Million
	Mode	NTSC/PAL Auto Adjust
Frequency	Horizontal Vertical	30 – 81 KHz 55 – 75 Khz
Response Time		8ms
Audio		2Wx2W
Resolution		1280 x 1024 @ 75 Hz
Power		Normal: 45W, Saving Mode: 5W
Input Signal		Composite Video: BNC(CVBS), S-VHS, VGA, Audio
Output Signal		Composite Video: BNC(CVBS), Audio
Video Color		NTSC or PAL
Wall Mount		VESA DPMS
Weight	Net: 5.4kg/11.88lbs, Packaging: 7.4kg, 16.28lbs	
Dimensions	495(W)x508(H)x54(D)mm, 19.49"x20"x2.32"	
Container Load	20ft/40ft, 400Sets/880 Sets	
Certification	UL, cUL, FCC, CE	

www.nanovdisplay.com